



## Accessories Production and Processing...

SHW21CA[1,2,3,4,5,6,7,8,9]  
 C1+[60-1900/1]L[H,P,SP,UP] THK  
 Linear Guide Caged Ball Wide Rail SHW  
 Accuracy and Preload Selectable

Bearing No.  
 SHW21CA[1,2,3,4,5,6,7,8,9]C1+[60-1900/1]L[H,  
 P,SP,UP]

SHW21CA[1,2,3,4,5,6,7,8,9]C1+[60-1900/1]L[H,P,SP,UP] Bearing 2D drawings and 3D CAD models

Days to Ship	9 Days
Block Type	[Wide] CA: Flanged w/Tapped Holes and Middle Holes
The number of LM blocks combined with a axis	1 ~ 9
Nominal Part Number	21
Rail Width W1	37 mm
Mounting Height M	21 mm
Material	Carbon Steel
Rail Length L	60 ~ 1900 mm
Radial Clearance	Light Preload
Accuracy Grade	High Grade / Precision Grade / Super Precision Grade / Extra High Precision Grade
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	8240
Basic Load Rating Static Rating Co(N)	12800
Allowable Static Moment MA(N m)	80.6
Allowable Static Moment MB(N m)	80.6



## Accessories Production and Processing...

Allowable Static Moment MC(N m)	229
Grease Nipple Option	None
Block external dimension W	68 mm
Block external dimension L	59 mm
Number of Block Mounting Holes(holes)	6
Mounting Hole Dimension S(M)	M5
Mounting Hole Screw Depth	Through mm
Block dimension L1	43.6 mm