



Accessories Production and Processing...

6CSR20S+[87-3000/1]/[87-3000/1]L[P,SP,U P] THK Cross-Rail Guide Block Set

Bearing No. 6CSR20S+[87-3000/1]/[87-3000/1]L[P,SP,UP]

6CSR20S+[87-3000/1]/[87-3000/1]L[P,SP,UP]
Bearing 2D drawings and 3D CAD models

Days to Ship	82 Days
Rail Width W1	20 mm
Mounting Height M	57 mm
Number of blocks	6
Rail Length L	87 ~ 3000 mm
Radial Clearance	Normal
Accuracy Grade	Precision Grade / High Precision Grade / Extra High Precision Grade
Callout Size	20
Length of Y axis Rail (Only Applies To The Cross- guide)	87 ~ 3000
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	13800
Basic Load Rating Static Rating Co(N)	23800
The outside dimension W of block	50.8 mm
The outside dimension L of block	74 mm
The number of mounting hole for blocks(piece)	2 × 2
Mounting Hole Dimension S(M)	M5
Mounting Hole Screw Depth	8 mm



Accessories Production and Processing...

Allowable static moment $M_o(N \cdot m)$	190
---	-----