



Accessories Production and Processing...

6CSR45C[0,1]+[188-3090/1]/[188-3090/1]L[P, SP,UP] THK Cross-Rail Guide Block Set

Bearing No.
6CSR45C[0,1]+[188-3090/1]/[188-3090/1]L[P,SP,UP]

6CSR45C[0,1]+[188-3090/1]/[188-3090/1]L[P,SP,UP] Bearing 2D drawings and 3D CAD models

Days to Ship	82 Days
Rail Width W1	45 mm
Mounting Height M	118 mm
Number of blocks	6
Rail Length L	188 ~ 3090 mm
Radial Clearance	Light Preload / Medium Precompression
Accuracy Grade	Precision Grade / High Precision Grade / Extra High Precision Grade
Callout Size	45
Length of Y axis Rail (Only Applies To The Cross-guide)	188 ~ 3090
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	80400
Basic Load Rating Static Rating Co(N)	127500
The outside dimension W of block	129.8 mm
The outside dimension L of block	170.8 mm
The number of mounting hole for blocks(piece)	2 × 5
Mounting Hole Dimension S(M)	M10



Accessories Production and Processing...

Mounting Hole Screw Depth	15 mm
Allowable static moment $M_o(N \cdot m)$	2430