



Accessories Production and Processing...

5SCR20C[0,1]+[111-2500/1]/[111-2500/1]L[P, SP, UP] THK Caged-Ball Cross Rail Linear Motion Guide Set

Bearing No.
5SCR20C[0,1]+[111-2500/1]/[111-2500/1]L[P,SP,UP]

5SCR20C[0,1]+[111-2500/1]/[111-2500/1]L[P,SP, UP] Bearing 2D drawings and 3D CAD models

Days to Ship	82 Days
Rail Width W1	20 mm
Mounting Height M	57 mm
Number of blocks	5
Rail Length L	111 ~ 2500 mm
Radial Clearance	Light Preload / Medium Precompression
Accuracy Grade	Precision Grade / High Precision Grade / Extra High Precision Grade
Callout Size	20
Length of Y axis Rail (Only Applies To The Cross-guide)	111 ~ 2500
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	28100
Basic Load Rating Static Rating Co(N)	50300
Allowable static moment MB(N · m)	568
The outside dimension W of block	78 mm
The outside dimension L of block	98 mm
Mounting Hole Dimension S(M)	M5



Accessories Production and Processing...

Mounting Hole Screw Depth	8 mm
The dimension L1 of bocks	43 mm
Allowable static moment Mo(N · m)	473